

# NORPAR™ 12 FLUID

Hydrocarbon Fluid

## Product Properties

Property	Test Method	Unit	Typical Value
Aniline Point	ASTM D 611	°C	83
Aromatics Content	UV	wt%	<0.01
Color	ASTM D 156	Saybolt	+30
Distillation range	ASTM D 86	°C	
Initial boiling point			189
Dry point			218
Flash Point	ASTM D 93 A	°C	69
Specific Gravity	ASTM D 4052	15.6 °C/15.6 °C	0.749

**Note:**

Values indicated describe typical physical properties and do not constitute specification limits.

U.S./Mexico/Canada

February 2005

©2005 ExxonMobil. The user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. ExxonMobil does not guarantee the typical (or other non-specification) values. Typical values only represent the values one would expect if the properties were tested in our laboratories with our test methods on the specified date. Some product properties are not frequently measured, and accordingly typical values may not be based upon a statistically relevant number of tests. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no warranty against patent infringement, not any endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward. EXXONMOBIL, the ExxonMobil Emblem, the "Interlocking X" Device, and NORPAR are trademarks of ExxonMobil.